



NUTRIFLO® Suction & Discharge Hose



APPLICATION: For handling almost every type of dry bulk food material or liquid in gravity flow and vacuum service. Nutriflo conforms to USDA Meat and Poultry, 3-A Sanitary, and FDA Standards and is used for the transmission of raw and pasteurized milk and other high water content dairy items.

CONSTRUCTION TUBE: Clear Pliovic® (FDA, 3-A, USDA compliant), NSF-61

COVER: Clear Pliovic

REINFORCEMENT: White or Clear high-density Pliovic® helix

TEMPERATURE: -15 °F to 158 °F (-26 °C to 70 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Not branded

1 2

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Color</u>	<u>Max. Working Pressure</u>	<u>Weight</u>
20013265	3/4 in 19.10 mm	0.990 in 25.20 mm	50.000 ft	CLEAR/WHITE	120.0 psi 0.83 MPa	0.18 lb/ft 0.27 kg/m
20013266	3/4 in 19.10 mm	0.990 in 25.20 mm	100.000 ft	CLEAR/WHITE	120.0 psi 0.83 MPa	0.18 lb/ft 0.27 kg/m
20013269	1 in 25.40 mm	1.240 in 31.50 mm	100.000 ft	CLEAR/WHITE	106.0 psi 0.73 MPa	0.260 lb/ft 0.39 kg/m
20013274	1 1/4 in 31.80 mm	1.550 in 39.40 mm	100.000 ft	CLEAR/WHITE	99.0 psi 0.68 MPa	0.360 lb/ft 0.54 kg/m
20013279	1 1/2 in 38.10 mm	1.780 in 45.20 mm	100.000 ft	CLEAR/WHITE	89.0 psi 0.61 MPa	0.430 lb/ft 0.64 kg/m
20013283	2 in 50.80 mm	2.370 in 60.20 mm	100.000 ft	CLEAR/WHITE	79.0 psi 0.54 MPa	0.670 lb/ft 1.00 kg/m

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Color</u>	<u>Max. Working Pressure</u>	<u>Weight</u>
20013287	2 1/2 in 63.50 mm	2.890 in 73.40 mm	100.000 ft	CLEAR/WHITE	65.0 psi 0.45 MPa	0.890 lb/ft 1.32 kg/m
20013290	3 in 76.20 mm	3.480 in 88.40 mm	100.000 ft	CLEAR/WHITE	65.0 psi 0.45 MPa	1.15 lb/ft 1.71 kg/m
20013293	4 in 101.60 mm	4.500 in 114.30 mm	100.000 ft	CLEAR/WHITE	55.0 psi 0.38 MPa	1.650 lb/ft 2.46 kg/m
20013297	6 in 152.40 mm	6.630 in 168.40 mm	100.000 ft	CLEAR/WHITE	47.0 psi 0.32 MPa	3.390 lb/ft 5.04 kg/m
20013329	1 in 25.40 mm	1.240 in 31.50 mm	100.000 ft	CLEAR	106.0 psi 0.73 MPa	0.260 lb/ft 0.39 kg/m
20013330	1 1/4 in 31.80 mm	1.550 in 39.40 mm	100.000 ft	CLEAR	99.0 psi 0.68 MPa	0.360 lb/ft 0.54 kg/m
20013331	1 1/2 in 38.10 mm	1.780 in 45.20 mm	100.000 ft	CLEAR	89.0 psi 0.61 MPa	0.430 lb/ft 0.64 kg/m
20013332	2 in 50.80 mm	2.370 in 60.20 mm	100.000 ft	CLEAR	79.0 psi 0.54 MPa	0.670 lb/ft 1.00 kg/m
20013333	2 1/2 in 63.50 mm	2.890 in 73.40 mm	100.000 ft	CLEAR	65.0 psi 0.45 MPa	0.890 lb/ft 1.32 kg/m
20013334	3 in 76.20 mm	3.480 in 88.40 mm	100.000 ft	CLEAR	65.0 psi 0.45 MPa	1.15 lb/ft 1.71 kg/m
20013335	4 in 101.60 mm	4.500 in 114.30 mm	100.000 ft	CLEAR	55.0 psi 0.38 MPa	1.650 lb/ft 2.46 kg/m
20013337	6 in 152.40 mm	6.630 in 168.40 mm	100.000 ft	CLEAR	47.0 psi 0.32 MPa	3.390 lb/ft 5.04 kg/m
20013268	1 in 25.40 mm	1.240 in 31.50 mm	50.000 ft	CLEAR/WHITE	106.0 psi 0.73 MPa	0.324 lb/ft 0.48 kg/m
20013278	1 1/2 in 38.10 mm	1.780 in 45.20 mm	50.000 ft	CLEAR/WHITE	89.0 psi 0.61 MPa	0.447 lb/ft 0.67 kg/m
20132399	2 in 50.80 mm	2.370 in 60.20 mm	50.000 ft	CLEAR/WHITE	79.0 psi 0.54 MPa	0.724 lb/ft 1.08 kg/m
20133208	2 in 50.80 mm	2.370 in 60.20 mm	25.000 ft	CLEAR/WHITE	79.0 psi 0.54 MPa	0.724 lb/ft 1.08 kg/m

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Color</u>	<u>Max. Working Pressure</u>	<u>Weight</u>
20133713	1 1/4 in 31.80 mm	1.550 in 39.40 mm	50.000 ft	CLEAR/WHITE	99.0 psi 0.68 MPa	0.360 lb/ft 0.54 kg/m
20133758	1 in 25.40 mm	1.240 in 31.50 mm	25.000 ft	CLEAR/WHITE	106.0 psi 0.73 MPa	0.324 lb/ft 0.48 kg/m
20134402	1 in 25.40 mm	1.240 in 31.50 mm	20.000 ft	CLEAR/WHITE	106.0 psi 0.73 MPa	0.324 lb/ft 0.48 kg/m