







**PM25**



**U-clamp**



**Mounting Flange**



Fillable



Custom Logo



Dials



Diaphragm Seal  
Compatible

## FEATURES / BENEFITS

- All-Welded Stainless Steel Construction
- Field Fillable Case, Nema 4X/IP65
- Economical Crimped Gauge with Heavy Duty Case Design
- Ideal for Both Indoor and Outdoor Applications



## SPECIFICATIONS

<b>Accuracy</b>	±1.6% ASME Grade B+, EN 837-1
<b>Ambient Limits</b>	-40°F/150°F
<b>Process Limits</b>	-40°F/250°F
<b>Process Limits with Diaphragm Seal</b>	Available with diaphragm seal, call to inquire.
<b>Wetted Materials</b>	Tube: 316SS Socket: 316SS
<b>Lens</b>	Polycarbonate (Standard), Tempered Glass, Laminated Safety Glass
<b>Other Materials</b>	Case: 304SS Ring: 304SS Dial: White Aluminum, Black Letters Case-to-Socket: Laser Welded
<b>Fillable</b>	Yes
<b>Maximum Working Pressure</b>	Stable = 100% Momentary = 130% of scale
<b>Environmental Protection</b>	NEMA 4X/IP65
<b>Weight</b>	2.5" = 0.35 lbs (0.5 lbs filled)