



| PART NO.  | A     | B     | C     | D     | E     |
|-----------|-------|-------|-------|-------|-------|
| 19MPX-.50 | .984  | .370  | .840  | .674  | 1.500 |
| 19MPX-.75 | .984  | .620  | 1.050 | .884  | 1.500 |
| 19MPX-1   | 1.984 | .870  | 1.315 | 1.097 | 1.125 |
| 19MPX-1.5 | 1.984 | 1.370 | 1.900 | 1.682 | 1.125 |
| 19MPX-2   | 2.516 | 1.870 | 2.375 | 2.157 | 1.125 |
| 19MPX-2.5 | 3.047 | 2.370 | 2.875 | 2.635 | 1.125 |
| 19MPX-3   | 3.579 | 2.870 | 3.500 | 3.260 | 1.125 |
| 19MPX-4   | 4.682 | 3.834 | 4.500 | 4.260 | 1.125 |
| 19MPX-5   | 5.687 | 4.782 | 5.563 | 5.295 | 2.000 |
| 19MPX-6   | 6.570 | 5.782 | 6.625 | 6.357 | 1.125 |

|   |                                      |              |
|---|--------------------------------------|--------------|
| TOLERANCES<br><br>REFER TO<br>STEEL & O'BRIEN<br>DOCUMENT # QS121 | <b>Steel &amp; O'Brien Mfg. Inc.</b> |              |
|   | TITLE<br>TC x SCH-10 BW              |              |
|   | DWG NO: <b>19MPX</b>                 | REV          |
|   | SCALE: N/A                           | SHEET 1 OF 1 |