



Part No.	Size	"A"	"B"	"C"	"D"
BLV2C-.50-NC-316	1/2"	3.50	6.62	2.45	7.66
BLV2C-.75-NC-316	3/4"	3.98	6.81	2.45	7.66
BLV2C-1-NC-316	1"	4.49	6.82	3.21	7.66
BLV2C-1.5-NC-316	1 1/2"	5.51	8.53	3.74	8.09
BLV2C-2-NC-316	2"	6.14	8.83	3.74	8.09
BLV2C-2.5-NC-316	2 1/2"	7.76	10.70	4.68	9.84
BLV2C-3-NC-316	3"	9.02	10.97	4.68	9.84
BLV2C-4-NC-316	4"	9.57	12.98	5.53	13.97

	TOLERANCES	DRAWN R Canell 7/30/2013	Steel & O'Brien Mfg. Inc.		
	DECIMALS: .XX ±.125 .XXX ±.050 ANGLES: 1°	UNLESS OTHERWISE NOTED: >ALL WELDS ARE AUTOGENOUS BUTTWELD >WELDS POLISHED FLUSH >32Ra ID/OD >REFER TO DOC# QS121 FOR GENERAL TOLERANCES	TITLE TC ACTUATED BALL VALVE (NORMALLY CLOSED)		
			DWG NO: BLV2C-NC		REV
			SCALE: NTS		SHEET 1 OF 1